

PRODUCT NAME:

AQUA THOMOND

PERMEABLE BLOCK PAVING



PRODUCT DESCRIPTION: Smooth finish Permeable blocks paving with chamfered edges defining sharp clean lines.

PRODUCTION STANDARD: I.S. EN 1338 Concrete paving blocks — Requirements and test methods

USE: Concrete block paving for use in Sustainable Urban Paving Systems (SuDS) the Aqua Thomond permeable block can be specified for all sites designed under BS7533-Pt13 and BBA certificate: 97/3373

TYPE: Permeable Concrete Block paving

FINISH/COLOUR: Antique Rustic Appearance

AVAILABLE IN 5 COLOURS:

1. Natural
2. Charcoal Grey
3. Curragh Blend
4. Causeway Blend
5. Limestone

AVAILABLE IN SIZES:

THICKNESS

1. 60mm for use in lightly traffic pavements, driveways, patios and footpaths.
2. 80mm for use in heavy duty pavements

WORKING SIZE

60mm Available in Mixed bail (Equal Number of each size)

- 160 x 160 x 60mm
- 240 x 160 x 60mm

80mm Available in single size

- 240x160mm x80mm

SPECIAL SHAPES: Kerbs & Channels available to match

INSTALLATION & MAINTENANCE: Laid to BS 7533 Pt. 13 and BBA certificate: 97/3373 and technical advice given in Roadstone Brochure Technical Section. Design service available

BUILD-UP/STONE SPECIFICATION:

Lower sub-base layer 10-63mm clean crushed stone

Upper sub-base layer 5-20mm clean crushed

Laying course 2-6mm clean crushed stone

Surface Dressing 2-4mm clean crushed stone

ANCILLARY COMPONENTS Exclusive to Roadstone / Formpave Aquaflow system

Inbitex Geotextile non-woven geotextile is used for separation, filtration and pollution control.

SC Intergrid sub-base stabilisation grid improves structural strength, increases design life and reduces construction costs.

SC Membrane This impermeable membrane allows the storage of collecting storm water. Used for the Aquaflow attenuation system it can be welded or taped dependent on the application. A higher grade SC Membrane GT can be specified when contamination is present.

SC Findrain This drainage component allows efficient and high flow removal of storm water from the Roadstone Aquaflow system. Wrapped in Inbitex Geotextile which provides further filtration and cleansing.

Aquaflow Distribution Tanks Voided crates that are extremely strong structurally and are wrapped in Inbitex

Geotextile, which provides filtration and cleansing. Allows the collection of impermeable surface water catchment, such as roofs to the Aquaflow system.

Also available from Roadstone Top Hats, Tape and Fittings