

Roadstone - leading supplier of building materials

Causeway Roof Tiles

The evolutionary new Causeway Roof Tile is a thin leading edge roof tile with a smooth or a riven texture finish. The Causeway Roof Tile offers contractors, specifiers, and home builders the beauty of a slate effect roof while keeping cost to a minimum.

Key features and benefits

- Quick and easy to install
- Reduced building costs
- Suits roof pitches from 22.5°

Technical specification

CRH Roof Tiles are manufactured to exacting standards at our various Roof Tile Plants. Manufacturing is in compliance with I.S. E.N. 490: 2005 Concrete Roofing Tiles & Fittings and should be fixed in accordance with the Irish Code of Practice for Slating and Tiling I.C.P. 2:2002.

Fixing Guide: Recommended Nailing/Clipping as per requirements given in compliance with I.C.P. 2:2002. The minimum recommended pitch may be influenced by certain restrictions. For advice on pitches between 22.5° and 17.5° please contact your local Roadstone location, which can be found [here](#).

Product sizes, weights & quantities

Size (overall)	Minimum Pitch	Maximum Pitch	Headlap
420 x 334mm	Nailed 25° Clipped 22.5°	90° (Over 55° subject to increased fixing)	Minimum 100mm

Related products

- [Ridges](#)
- [Rapid Roll-Out Ridge](#)
- [Stepped Dry Verge](#)
- [Tile Vent](#)