
Roadstone - leading supplier of building materials

Continuous Dry Verge

The Roadstone Continuous Dry Verge System provides a neat, mortar-free verge that eliminates the need for undercloak.

Nail fixing provides high resistance to wind uplift for both verge tiles and the verge extrusion. Continuous Dry Verge is available in two sizes: (a) 93mm (b) 105mm profiled tiles.

Key features and benefits

- Provides continuous cover and clean visual line to verge
- Provides continuous weatherproof cover along gable verges
- Provides increased strength and high security against occurrence of wind damage
- Easy to fix without the use of special tools or adhesives
- No requirement for mortar bedding or slate undercloak
- Saves time and labour
- Can be fitted in poor weather conditions
- Provides a complementary finish to PVC bargeboards, fascias and soffits
- Available for use with all Roadstone tile profiles
- Supplied in 3m lengths
- Connectors available for joints
- Available in a range of colours

Technical specification

CRH Roof Tiles are manufactured to exacting standards at our various Roof Tile Plants. Manufacturing is in compliance with I.S. E.N. 490: 2005 Concrete Roofing Tiles & Fittings and should be fixed in accordance with the Irish Code of Practice for Slating and Tiling I.C.P. 2:2002

Related products

- [Dry Hip System](#)
- [Dry Vent Ridges](#)
- [Stepped Dry Verge](#)
- [Donard Roof Tile](#)
- [Ridges](#)