

Roadstone - leading supplier of building materials

Donard Roof Tile

Donard Roof Tile

The Donard Roof Tile has a traditional flat pattern profile offering the clean lines and smart finish of an interlocking slate pattern. The Donard Roof Tile has a smooth finished flat leading edge with good wind loading and anti-capillary features, which is ideal for performing in the Irish climate. The roof tile is a true black pigmented tile.

Key features and benefits

- Quick and easy to install
- Reduced building costs
- Suits roof pitches from 22.5°
- Enhances the traditional design of a building

Technical specification

CRH Roof Tiles are manufactured to exacting standards at our various Roof Tile Plants. Manufacturing is in compliance with I.S. E.N. 490: 2005 Concrete Roofing Tiles & Fittings and should be fixed in accordance with the Irish Code of Practice for Slating and Tiling I.C.P. 2:2002.

Fixing Guide: Recommended Nailing/Clipping as per requirements given in compliance with I.C.P. 2:2002. The minimum recommended pitch may be influenced by certain restrictions. For advice on pitches between 22.5° and 17.5° please contact your local Roadstone location, which can be found [here](#).

Product sizes, weights & quantities

Size (overall)	Minimum Pitch	Maximum Pitch	Minimum Headlap
419 x 334mm	Nailed 25° Clipped 22.5°	90° (Over 55° subject to increased fixing)	30° and over - 75mm Less than 30° - 100mm

Related products

- [Ridges](#)
- [Rapid Roll-Out Ridge](#)
- [Dry Vent Ridges](#)

-
- [Continuous Dry Verge](#)
 - [Dry Hip System](#)