

# Roadstone - leading supplier of building materials

## Gemini Roof Tiles

Gemini Twintile

Gemini TwinTile is an interlocking tile which is 270mm x 330mm overall. With its carefully judged central groove, the tile gives the appearance of two plain tiles side by side when laid. With a laid weight of just 50kg per metre square it is equally as cost effective for refurbishment as for a new build.

### Frequently Asked Questions on Gemini Twintile

## Key features and benefits

- Only 17.5 tiles per m<sup>2</sup> (60 for plain tiles)
- Lays to 25° (35° for plain tiles)
- 30% reduction in weight
- 42% timber savings on roof battens
- 6% saving on roof trusses
- Full range of Dry Fix fittings available

## Technical specification

CRH Roof Tiles are manufactured to exacting standards at our various Roof Tile Plants. Manufacturing is in compliance with I.S. E.N. 490: 2005 Concrete Roofing Tiles & Fittings and should be fixed in accordance with the Irish Code of Practice for Slating and Tiling I.C.P. 2:2002.

## Product sizes, weights & quantities

Size (overall)	Minimum Pitch	Maximum Pitch	Headlap
Standard Slate - 270 x 337mm	25°	90° (Over 55° subject to increased fixing)	Minimum - 80mm
Slate and a half - 270 x 495mm			Maximum - 95mm

## Related products

- [Minislate](#)
- [Dry Hip System](#)
- [Ridges](#)
- [Continuous Dry Verge](#)
- [Rapid Roll-Out Ridge](#)

