

MORTAR & RENDER

Approximate Spread Rates – No allowance for waste

1. FLOMIX MORTAR

1 tonne of Flomix will lay (10mm joint):	
1300	Standard Bricks
650	100mm Solids on Edge
325	100mm Solids on Flat
325	215mm Hollows

1.40 tonne of Dry Flomix Mortar @ 16.5% water content = approx. 1m³ of Fresh Mortar

16 tonne of Dry Flomix Mortar = approx. 11.5m³ of Fresh Mortar approx.

2. FLOMIX RENDER

1 tonne of Flomix Silo Render when mixed will cover:	
10mm thick	69m ² approx.
12mm thick	55m ² approx.
15mm thick	34m ² approx.
24mm thick	27m ² approx.

16 tonne of Dry Silo Render = approx. 11m³ of Fresh Render @ 15 / 16% water content for workability.

3. TROWEL READY MORTAR

Approximate Spread Rates – no allowance for waste, using 10mm joint. 1m ³ will lay:	
1800	Standard Bricks
900	100mm Solids on Edge
450	100mm Solids on Flat
450	215mm Hollows

4. FLOAT READY PLASTER (APPROXIMATE COVERAGE)

1m ³ will cover:	
100m ²	@ 10mm thick
80m ²	@ 12mm thick
66m ²	@ 15mm thick
40m ²	@ 25mm thick